



SRC Conformable	.047 (OD)	.085 (OD)	.141 (OD)	.250 (OD)
CenterConductor	SCCS	SCCS	SCCS	SC
Dimension in. (mm)	.007 (.18)	.020 (.51)	.036 (.91)	.065 (1.65)
Dielectric	TFE .033	TFE .066	TFE .116	TFE .209
Jacket	Cu/Sn Composite	Cu/Sn Composite	Cu/Sn Composite	Cu/Sn Composite
Min. Inside Bend in. rad	.125"	.125"	.250"	.375"
Impedance	50	50	50	50
Capacitance	30.0	29.5	29.3	29.6
Velocity of Propogation	70%	70%	70%	70%
Max Voltage vrms	1000	1500	1900	5000
Frequency Range	DC to 20GHz	DC to 20GHz	DC to 20GHz	DC to 18GHz
Temperature range °C	-65+150	-65+150	-65+150	-65+150
Attenuation (db/100ft)				
.5GHz	25.0	15.0	8.0	4.4
1GHz	36.0	22.0	12.0	6.7
10GHz	128	83.0	45.0	27.0
15GHz	162	120	65.0	36.0
20GHz	192	126	70.0	NA
Power (W)				
.5GHz	45	180	600	1900
1GHz	32.5	130	450	1400
10GHz	13	35	120	350
15GHz	11	26	88	200
20GHz	10.5	20	70	NA

All Rights Reserved | © SRC Cables, Inc.
 5590 Skylane Boulevard, Santa Rosa, CA
 (707) 573-1900; info@src-cables.com

ERROR: undefined
OFFENDING COMMAND:

STACK: